

LINE-INTERACTIVE UPS · SERIE LA-VST-RG

Flexible backup with 8 Schuko outlets

Battery backup and surge protection for workstations and mobile devices.

SERIE **LA-VST-RG**



Line-interactive AVR
TECHNOLOGY

2 models
LA-VST-900RG · 1200RG

Tower
FORMAT

IDEAL FOR

Workstations

Peripherals

Home office

CCTV

QUICK DECISION

The essentials, at a glance

Key figures for the range



POWER
900 / 1200 VA



OUTPUTS
8 x Schuko



USB CHARGING
5 V / 2,1 A



BACKUP TIME
15 / 18 min

TECHNICAL ADVANTAGES

Key features

- Line-interactive UPS
- Modified sine wave
- Built-in AVR to ensure voltage stability
- LED indicators
- Charging in Off mode
- 8 Schuko outlets with surge protection, 4 with battery backup
- Cold start function
- Microprocessor control that ensures reliability



3-year electronics warranty
2-year battery warranty



Free pickup & return service
Only applicable in the Iberian Peninsula



Technical specifications

SERIE LA-VST-RG | LINE-INTERACTIVE UPS

LAPARA
Energy Networks

MODEL	LA-VST-900RG	LA-VST-1200RG
CAPACITY	900 VA / 480 W	1200 VA / 600 W
INPUT		
Voltage	220/230/240 VAC (default: 230 VAC)	
Voltage range	162-268VAC / 170-280VAC / 177-290VAC	
Frequency range	50/60 Hz ± 5Hz (auto-sensing)	
OUTPUT		
Voltage	220/230/240 VAC (default: 230 VAC)	
AC voltage regulation (Battery Mode)	±10%	
Frequency range (Battery Mode)	60 Hz or 50 Hz ±1 Hz	
Transfer time	Typical 2-6 ms, 10ms max.	
Waveform (Battery Mode)	Modified sine wave	
BATTERY		
Battery type and quantity	12V / 9AH x 1	
Backup time (with 1 PC @ 120W)	15 min.	18 min.
Typical recharge time	6 - 8 hours to 90% capacity	
INDICATORS		
AC Mode	Green LED	
Battery mode	Yellow LED flashes	
Fault	Red LED	
PROTECTION		
Full protection	Overload, discharge and overcharge protection	
ALARM		
Battery mode	Sounding every 10 seconds	
Low battery	Sounding every second	
Overload	Sounding every 0.5 seconds	
Fault	Sounding continuously	
INTERFACE		
Output connections	4 x Schuko (battery backup) + 4 x Schuko (surge-protected)	
Charging port	1 x USB (5V / 2.1A)	
PHYSICAL DATA		
Dimensions, D x W x H (mm)	345 x 200 x 100	
Net weight (kg)	5,5	6,4
OPERATING ENVIRONMENT		
Humidity	0-90 % RH @ 0-40°C (non-condensing)	
Noise level	Less than 40dB	

* Specifications subject to change without notice. Please refer to the applicable service conditions.